



DRY - SPEED

Electrode Drying - Keeping Oven Inox

Our company EMPORIKI GROUP responding to the demands of the users for the placement of 2 different diameter electrodes in the drying ovens, produced a NEW product with an internal perforated stainless steel separator. The separator makes easier the placement of the different types of electrodes in the oven, saving valuable time for the user. The supreme INOX construction along with the high quality insulation grants to this NEW product a quality advantage, in order to be added to the already tested high quality series with absolute success. This NEW series includes:

Φουρνάκια Αποξήρανσης - Συντήρησης Ηλεκτροδίων Inox

Η εταιρεία μας ΕΜΠΟΡΙΚΗ GROUP ανταποκρινόμενη στην νέα απαίτηση των χρηστών για τοποθέτηση 2 διαμέτρων ηλεκτροδίων στο ίδιο φουρνάκι παρήγαγε ΝΕΟ προϊόν με ενδιάμεσο διαχωριστή για εύκολη τοποθέτηση και παραλαβή των 2 διαφορετικών διαμέτρων ηλεκτροδίων ή ποιότητων. Η στιβαρή INOX κατασκευή σε συνδυασμό με την υψηλής ποιότητας μόνωση δίνουν ένα ποιοτικό προβάδισμα στο ΝΕΟ αυτό προϊόν ώστε να συμπληρώσει την δοκιμασμένη παλαιά σειρά παραγωγής με επιτυχία. Η νέα αυτή σειρά περιλαμβάνει:

10
kgr

60° - 350° C

ELECTRODE DRYING OVEN INOX (2 compartments)

CODE No	DESCRIPTION	type
070010011	220V, 400 W, capacity 10 kgr, with temperature regulator, 60°-350° C, 2 compartments, special thermal insulation	SS-10P

TECHNICAL CHARACTERISTICS:

MODEL	CAPACITY	ELECTR. SUPPLY	MAX TEMP.	HEIGHT	WIDTH	DEPTH	WEIGHT	THERMAL INSULATION
070010011	10 kgr	220V 400 watt	350° C	550 mm	145 mm	145 mm	6 kgr	YES

10
kgr

50° - 200° C

ELECTRODE KEEPING OVENS INOX WITH INSULATION (2 COMPARTMENTS) 10 KGR 50°-200°.

CODE No.	DESCRIPTION	TYPE
070010012	32/85V, 250W, CAPACITY 10KGR WITH TEMPERATURE REGULATOR, 50°-200°, 2 COMPARTMENTS, WITH 2 CABLE CONNECTOR.	SS-11P
070010010	110V, 250W, CAPACITY 10 KGR WITH TEMPERATURE REGULATOR, 50°-200°, 2 COMPARTMENTS	SS-09P
070010009	220V, 300W, CAPACITY 10KGR WITH TEMPERATURE REGULATOR, 50°-200°, 2 COMPARTMENTS	SS-08P

TECHNICAL CHARACTERISTICS:

CODE	CAPACITY	ELECTR. SUPPLY	MAX TEMP.	HEIGHT	WIDTH	DEPTH	WEIGHT	THERMAL INSULATION
070010012	10 kgr	32/85V 300 watt	200° C	550 mm	145 mm	145 mm	6 kgr	YES
070010010	103 kgr	110V 300 watt	200° C	550 mm	145 mm	145 mm	6 kgr	YES
070010009	10 kgr	220V 300 watt	200° C	550 mm	145 mm	145 mm	6 kgr	YES

